

Specification sheet

S 6000 Cambio Excellence in technology and design – For high demands



Variations	Sub-frame	No. of compart ments	Height	Compartment width	Depth
Full height lockers	Feet	1-4	1980 mm	300/400 mm	525 mm
	Plinth	1-4	1950 mm	300/400 mm	525 mm
Double-tier lockers	Feet	1-4	1980 mm	300/400 mm	525 mm
	Plinth	1-4	1950 mm	300/400 mm	525 mm
Assembled box lockers, 3-6 tiers	Feet	1-4	1980 mm	300/400 mm	525 mm
	Plinth	1-4	1950 mm	300/400 mm	525 mm
Z lockers, 2 rooms per soompartment	Feet	1-4	1980 mm	300/400 mm	525 mm
	Plinth	1-4	1950 mm	300/400 mm	525 mm
Corner lockers, full	Feet	1	1980 mm	-	500/213 mm
height and 2 tiers	Plinth	1	1950 mm	-	500/213 mm

Construction details:

Carcass	Durable sheet steel construction with overlapping doors– material thickness 0,88 mm 54° slope on the body interior – for high stability and an easy, convenient way to remove clothing
	New ventilation system with the SVL concept [®] as standard feature. Other
	ventilations systems are also available, please ask for details.
	Optimal air circulation via predefined ventilation spaces in front of and behind the hat shelf
	Body and steel doors electrolytically zinc-plated as a standard
	Sub-frame alternatively with feet, base, storage box, or bench
Doors	Fronts made of steel (single-walled or optionally double-walled) or HPL (optional) with wood decor for an even more attractive appearance. HPL decor doors available in white, silver gray, birch, cherry, and wengé Door hinges for sheet steel doors made of aluminum/plastic Door hinges for HPL decor fronts made of stainless steel
	Door opening limiter 90° for outstanding closing characteristics as standard fittings
Interior	Wide variety of interior fitting solutions for any requirement Sturdy wardrobe rail made of oval profile, 4 twist-proof hooks with system holder, e.g. for coat hangers or movable partitions
	Slot-in shoe shelf, can be easily retrofitted by users
Locks	Cylinder lock with 2 keys as standard.
Colors	C+P standard colors
Options:	
Feet	Height adjustment through adjustable plastic feet 130 mm high, can be easily adjusted from inside and outside
Plinth	Steel plinth, 100 mm. Height adjustable
Bench	Substructures and corner solutions with bench underneath, with storage box, with corner panel for inside corners, as corner locker for inside or outside corners and double locker for outside corners. Ask for more details.
Locks	Safety turning bolt latch for padlock, Cylinder lock with or without master key system Cylinder locks in moisture-proof design Coin locks
	Digilocks Mechanical combination lock
	Ask for other locking systems
Accessories	Number plates, plastic key rings, wristband for keys, padlocks, sloping top, additional interior fittings, top lockers, different kind of door finish


Details and options:



Single-wall doors with closed side profiles for greatest stability and anti-theft security.



Double-wall doors with insulation; sandwich construction with



HPL = high pressure laminate (high-density solid core compact panel with decor).



good sound absorption.

New door opening limiter 90°: Made from special heavyduty, plastic-coated stainless . steel cable. Standard design for all steel and decor doors.

Door hinge of stainless steel for decor doors.

Easy height adjustment: Cambio's corrosion-free plastic feet can be height adjusted from the inside and from the outside.





Door hinge of aluminum diecast/ plastic for steel doors.

54° profile in the body: This innovative profile makes the locker even more stable and secure. Also, the interior can be cleaned and clothing can be removed more easily.

SVL concept: Perforations that are located with the ventilation requirements in mind ensure the optimal flow of air.



3