

icon glass product summary



Features:

Visible full aluminium frame.

Standard height of 2000mm with 150mm floor gap.

Available in full height version up to 2500mm with 100mm floor gap (as Icon Glass Tall).

Finished door thickness is either 10mm back painted glass or 10.76mm laminated glass.

Anti-fingertrap feature.

Concealed self-closing door closer in foot.

Pivoted door.

Aluminium fittings.

Machined aluminium lock locates into post.

Glass can match any RAL colour.

Emergency release.

10 year warranty.

Also available in:

- Wood Veneer
- Stainless Steel
- Aluminium
- CGL
- HPL



thrislington cubicles

t +44 1244 520 677
e info@thrislingtoncubicles.com
www.thrislingtoncubicles.com

Warranty: 10 Years.

Tested: 200,000 operations.

Made in the UK



thrislington cubicles

t +44 1244 520 677
e info@thrislingtoncubicles.com
www.thrislingtoncubicles.com

K32 Specification: Icon Glass Cubicles

Specification: Overall cubicle height up to 2000mm with 150mm floor clearance, supplied with a 10 year warranty.

Framework: Full anodised aluminium frame using Aluminium Alloy 6063T6 having a 20 micron anodised finish and with 60% recycled content, comprising extruded headrail and vertical posts. Lock locates directly into vertical closing post, incorporating full length buffer.

Door: 10mm back painted toughened glass or 10.76mm toughened laminated glass, polished to all edges. Flush aluminium studs secured through the door to the aluminium pivot brackets, allow the door to pivot between a structural aluminium headrail and engineered aluminium foot, hand-turned in UK. Foot incorporates height adjustment and sealed bearing providing self-closing mechanism (alternatively, the mechanism can be factory set to fall open). Complete with anti-finger trap clearance on pivot side of door.

Divider: 10mm back painted toughened glass or 10.76mm toughened laminated glass, polished to all edges. Supported 150mm from the floor by an engineered anodised aluminium foot, hand-turned in UK, with height adjustment.

Fascia: Where required, 10mm back painted toughened glass or 10.76mm toughened laminated glass, polished to all edges. If a fascia exceeds the width of 150mm, it will need to be supported by an engineered aluminium foot.

Fittings: Precision engineered anodised aluminium lock, hand-turned in UK and able to be opened with a closed fist, is fixed through the door to the face plate for added strength. Incorporating a machined aluminium bar, with a sacrificial hard nylon shear tip, which locates into the vertical closing post. Complete with emergency release facility. Divider fixed to back wall using through-fixed extruded aluminium brackets. Aluminium coat hook supplied as standard. Components tested over a cycle of 200,000 operations, equating to a 10 year period in a medium use washroom.

Finishes:

Door: 10mm back painted toughened glass or 10.76mm toughened laminated glass from our standard colour range. Glass may be clear or low-iron and can be supplied at set levels of obscurity.

Divider: 10mm back painted toughened glass or 10.76mm toughened laminated glass from our standard colour range. Glass may be clear or low-iron and can be supplied at set levels of obscurity.

Fascia: 10mm back painted toughened glass or 10.76mm toughened laminated glass from our standard colour range. Glass may be clear or low-iron and can be supplied at set levels of obscurity.

