


oasis compact grade product summary



Features:

Visible full aluminium frame.

Standard height of 2000mm with 150mm floor gap.

Available up to 2700mm with 15mm floor gap (as Oasis Full Height).

Finished door thickness of 12mm.

Self-closing hydraulic door closer.

Pivoted door.

Stainless steel fittings.

Precision engineered stainless steel lock with flush face plate, hand turned in UK, able to be opened using a closed fist.

Lock locates into integral receiver.

Wide range of compact grade laminates available, from various leading manufacturers.

Emergency release.
10 year warranty.

Also available in:

- Glass
- Wood Veneer
- Stainless Steel
- Aluminium
- HPL



thrislington cubicles

t +44 1244 520 677
e info@thrislingtoncubicles.com
www.thrislingtoncubicles.com

Warranty: 10 Years.

Tested: 200,000 operations.

Made in the UK



thrislington cubicles

t +44 1244 520 677
e info@thrislingtoncubicles.com
www.thrislingtoncubicles.com

K32 Specification: Oasis Compact Grade Cubicles

Specification: Overall cubicle height up to 2000mm with 150mm floor clearance, supplied with a 10 year warranty.

Framework: Full anodised aluminium frame using Aluminium Alloy 6063T6 having a 5 micron anodised finish and with 60% recycled content, comprising extruded headrail and vertical posts. Precision engineered stainless steel lock, hand-turned in UK, locates into integral receiver within vertical closing post, incorporating full length buffer.

Door: 12mm compact grade laminate, polished to all edges. Stainless steel fixings to the face of the door allow attachment to stainless steel pivot blocks. Door suspended from a structural aluminium headrail and located onto a unique bottom pivot bracket, falls closed by means of a hydraulic closer designed specifically for the purpose, concealed within the aluminium headrail (alternatively, the closer can be factory set to fall open).

Divider: 12mm compact grade laminate, polished to visible edges. Supported 150mm from the floor by a precision engineered 304 grade stainless steel foot, hand-turned in UK, with height adjustment.

Fascia: Where required, 12mm compact grade laminate, polished to visible edges. If a fascia exceeds the width of 100mm, it will need to be supported by a precision engineered 304 grade stainless steel foot.

Fittings: Precision engineered 303 grade brushed stainless steel lock, hand-turned in UK, and able to be opened using a closed fist, is fixed through the door to the face plate for added strength. Incorporating a machined stainless steel bar, with a sacrificial hard nylon shear tip, which locates into the receiver within the vertical closing post. Complete with emergency release facility and buffer. Divider fixed to back wall using visible brackets, secured by through-fixings. Stainless steel coat hook supplied as standard. Components tested over a cycle of 200,000 operations, equating to a 10 year period in a medium use washroom.

Finishes:

Door: 12mm compact grade laminate from our standard ranges, which include various leading manufacturers.

Divider: 12mm compact grade laminate from our standard ranges, which include various leading manufacturers.

Fascia: 12mm compact grade laminate from our standard ranges, which include various leading manufacturers.

