

## oasis full height compact grade product summary



### Features:

Visible full aluminium frame.

Available up to 2700mm with 15mm floor gap.

Also available at a standard height of 2000mm with a 150mm floor gap.

Where the cubicle exceeds 2200mm in height, the finished door thickness increases from 12mm to 18mm.

Anti-fingertrap.

Self-closing hydraulic door closer.

Pivoted door.

Stainless steel fittings.

Precision engineered stainless steel lock with flush face plate, hand turned in UK, able to be opened using a closed fist.

Lock locates into integral receiver.

Wide range of laminates available, from various leading manufacturers.

Emergency release.

10 year warranty.

Also available in:

- Glass
- Wood Veneer
- Stainless Steel
- Aluminium
- HPL



**thrislington cubicles**

t +44 1244 520 677  
e [info@thrislingtoncubicles.com](mailto:info@thrislingtoncubicles.com)  
[www.thrislingtoncubicles.com](http://www.thrislingtoncubicles.com)

**Warranty:** 10 Years.

**Tested:** 200,000 operations.

**Made in the UK**



**thrislington cubicles**

t +44 1244 520 677  
e info@thrislingtoncubicles.com  
www.thrislingtoncubicles.com

### **K32 Specification: Oasis Full Height Compact Grade**

**Specification:** Overall cubicle height up to 2700mm with 15mm floor clearance, supplied with a 10 year warranty.

**Framework:** Full anodised aluminium frame using Aluminium Alloy 6063T6 having a 5 micron anodised finish and with 60% recycled content, comprising extruded headrail and vertical posts. Precision engineered stainless steel lock, hand-turned in UK, locates into integral receiver within vertical closing post, incorporating full length buffer.

**Door:** 18mm compact grade laminate, polished to all edges. Stainless steel fixings to the face of the door allow attachment to stainless steel pivot blocks. Door suspended from a structural aluminium headrail and located onto a unique floor fixed pivot bracket, falls closed by means of a hydraulic closer concealed within the aluminium headrail (alternatively, the closer can be factory set to fall open).

**Divider:** 12mm compact grade laminate, polished to visible edges. Suspended 15mm from the floor.

**Fascia:** Where required, 18mm compact grade laminate, polished to visible edges. Suspended 5mm from the floor.

**Fittings:** Precision engineered 303 grade brushed stainless steel lock, hand-turned in UK, and able to be opened using a closed fist, is fixed through the door to the face plate for added strength. Incorporating a machined stainless steel bar, with a sacrificial hard nylon shear tip, which locates into the receiver within the vertical closing post. Complete with emergency release facility and buffer. Divider fixed to back wall using visible brackets, secured by through-fixings. Stainless steel coat hook supplied as standard. Components tested over a cycle of 200,000 operations, equating to a 10 year period in a medium use washroom.

#### **Finishes:**

**Door:** 18mm compact grade laminate from our standard ranges, which include various leading manufacturers.

**Divider:** 12mm compact grade laminate from our standard ranges, which include various leading manufacturers.

**Fascia:** 18mm compact grade laminate from our standard ranges, which include various leading manufacturers.

