

oasis glass product summary



Features:

Visible full aluminium frame.

Standard height of 2000mm with 150mm floor gap.

Available up to 2700mm with 15mm floor gap (as Oasis Full Height).

Finished door thickness of either 10mm back painted glass or 10.76mm laminated glass

Self-closing hydraulic door closer.

Pivoted door.

Stainless steel fittings.

Precision engineered stainless steel lock with flush face plate, hand turned in UK, able to be opened using a closed fist.

Lock locates into integral receiver.

Glass can be back painted or laminated and can match any RAL colour.

Emergency release.

10 year warranty.

Also available in:

- Wood Veneer
- Stainless Steel
- Aluminium
- CGL
- HPL



thrislington cubicles

t +44 1244 520 677
e info@thrislingtoncubicles.com
www.thrislingtoncubicles.com

Warranty: 10 Years.

Tested: 200,000 operations.

Made in the UK



thrislington cubicles

t +44 1244 520 677
e info@thrislingtoncubicles.com
www.thrislingtoncubicles.com

K32 Specification: Oasis Glass Cubicles

Specification: Overall cubicle height up to 2000mm with 150mm floor clearance, supplied with a 10 year warranty.

Framework: Full anodised aluminium frame using Aluminium Alloy 6063T6 having a 5 micron anodised finish and with 60% recycled content, comprising extruded headrail and vertical posts. Precision engineered stainless steel lock, hand-turned in UK, locates into integral receiver within vertical closing post, incorporating full length buffer.

Door: 10mm back painted toughened glass or 10.76mm toughened laminated glass, polished to all edges. Countersunk stainless steel pig-nose fixings to the face of the door allow attachment to stainless steel pivot blocks. Door suspended from a structural aluminium headrail and located onto a unique bottom pivot bracket, falls closed by means of a hydraulic closer designed specifically for the purpose, concealed within the aluminium headrail (alternatively, the closer can be factory set to fall open).

Divider: 10mm back painted toughened glass or 10.76mm toughened laminated glass, polished to all edges. Supported 150mm from the floor by a precision engineered 304 grade stainless steel foot, hand-turned in UK, with height adjustment.

Fascia: Where required, 10mm back painted toughened glass or 10.76mm toughened laminated glass, polished to all edges. If a fascia exceeds the width of 100mm, it will need to be supported by a precision engineered 304 grade stainless steel foot.

Fittings: Precision engineered 303 grade brushed stainless steel lock, hand-turned in UK, and able to be opened using a closed fist, is fixed through the door to the face plate for added strength. Sacrificial hard nylon shear tip to the lock finger, which locates into the receiver within the vertical closing post. Complete with emergency release facility and buffer. Divider fixed to back wall using visible stainless steel brackets, secured by through-fixings. Stainless steel coat hook supplied as standard (height to be specified) Components tested over a cycle of 200,000 operations, equating to a 10 year period in a medium use washroom.

Finishes:

Door: 10mm back painted toughened glass or 10.76mm toughened laminated glass from our standard colour range. Glass may be clear or low-iron and can be supplied at set levels of obscurity.

Divider: 10mm back painted toughened glass or 10.76mm toughened laminated glass from our standard colour range. Glass may be clear or low-iron and can be supplied at set levels of obscurity.

Fascia: 10mm back painted toughened glass or 10.76mm toughened laminated glass from our standard colour range. Glass may be clear or low-iron and can be supplied at set levels of obscurity.

