



NOTE:
 GLASS THICKNESS DEPENDANT UPON
 PARTITION HEIGHT & LAYOUT REQUIRED

MANIFESTATION TO GLASS FROM THE FINISHED
 FLOOR LEVEL MUST BE INSTALLED IN ACCORDANCE
 WITH DOCUMENT 'M' BUILDING REGULATIONS

ALL GLASS MUST CONFORM TO
 BS 6262 & DOCUMENT
 'N' BUILDING REGULATIONS

ALL DIMENSIONS ARE NOMINAL & IN mm

DOOR WIDTH DIM X	DISTANCE BETWEEN SJ2 & SJ3 BASE CHANNEL DIM Z
835 (single)	925
1685* (double)	1765

* INCLUDES 5mm GAP BETWEEN DOORS



© COPYRIGHT & DESIGN 2007 PROPERTY OF
 KOMFORT WORKSPACE Plc
 WHITTLE WAY, CRAWLEY, WEST SUSSEX, RH10 9RT
 TEL : 01293 592500 WEB www.komfort.com
 DO NOT SCALE IF IN DOUBT ASK

ISSUE	DESCRIPTION OF CHANGE	DATE	TITLE	ISSUE
		02.05.07	POLAR SINGLE GLAZED GLASS DOOR MODULE HORIZONTAL USING SJ35 DOOR FRAME SECTION	1
MATERIAL :	CHKD	SSG	DRAWING NO	
FINISH :	SCALE	NTS	13086	