



GLASS THICKNESS DEPENDANT UPON PARTITION HEIGHT & LAYOUT REQUIRED

MANIFESTATION TO GLASS FROM THE FINISHED FLOOR LEVEL MUST BE INSTALLED IN ACCORDANCE WITH DOCUMENT 'M' BUILDING REGULATIONS

ALL GLASS MUST CONFORM TO BS 6262 & DOCUMENT 'N' BUILDING REGULATIONS

ALL DIMENSIONS ARE NOMINAL & IN mm

**NOTE: SCREWS FOR HINGE FIXINGS TO BE MAXIMUM 25mm LONG**

DOOR WIDTH DIM X	DISTANCE BETWEEN SJ4 & SJ3 BASE CHANNEL DIM Z
838 (SINGLE)	929
1678* (DOUBLE)	1769* (DOUBLE)

\* INCLUDES 2mm GAP BETWEEN DOORS



© COPYRIGHT & DESIGN 2007 PROPERTY OF  
 KOMFORT WORKSPACE Plc  
 WHITTLE WAY, CRAWLEY, WEST SUSSEX, RH10 9RT  
 TEL : 01293 592500 WEB www.komfort.com  
 DO NOT SCALE IF IN DOUBT ASK

ISSUE	DESCRIPTION OF CHANGE	DATE	TITLE	ISSUE
		08-06-07	POLAR SINGLE GLAZED TIMBER DOOR MODULE HORIZONTAL DETAIL WITH TIMBER DOOR FRAME	2
MATERIAL :		CHKD	DRAWING No	
FINISH :		SCALE	13106	