



THIS IS A NON FIRE PERFORMANCE ASSEMBLY
 MANIFESTATION 1500mm FROM THE FINISHED FLOOR LEVEL MUST BE INSTALLED IN ACCORDANCE WITH DOCUMENT 'N' BUILDING REGULATIONS WHEN BLINDS ARE NOT INCLUDED
 ALL GLASS MUST CONFORM TO BS 6262 & DOCUMENT 'N' BUILDING REGULATIONS
 ALL DIMENSIONS ARE NOMINAL & IN mm

NOTE: SCREW FIXING FOR HINGES TO BE MAXIMUM 25mm LONG

DOOR WIDTH DIM X	DISTANCE BETWEEN S/J4 & S/J3 BASE CHANNEL DIM Z
838 (SINGLE)	929
1678* (DOUBLE)	1769* (DOUBLE)

* INCLUDES 2mm GAP BETWEEN DOORS



© COPYRIGHT & DESIGN 2007 PROPERTY OF
 KOMFORT WORKSPACE Plc
 WHITTLE WAY, CRAWLEY, WEST SUSSEX, RH10 9RT
 TEL : 01293 592500 WEB www.komfort.com
 DO NOT SCALE IF IN DOUBT ASK

ISSUE	DESCRIPTION OF CHANGE	DATE	TITLE	ISSUE
		16:08:07	DOUBLE GLAZED POLAR TIMBER DOOR MODULE IN TIMBER DOOR FRAME HORIZONTAL DETAIL	1
MATERIAL :		DRAWN	SSG	
FINISH :		CHKD		
		SCALE	NTS	
			DRAWING No	14098