



DOOR WIDTH DIM X	DISTANCE BETWEEN SJ2 & SJ3 BASE CHANNEL DIM Z
838 (single)	924
1680* (double)	1766

* INCLUDES 4mm GAP BETWEEN DOORS

ALL GLASS MUST CONFORM TO
BS 476:PART 22
BS 6262, BS 6206 & DOCUMENT
'N' BUILDING REGULATIONS

FOR FIRE PERFORMANCE

DRAWING MUST BE READ IN CONJUNCTION WITH
SUMMARY OF PERFORMANCE DOCUMENT PO/F8
AND DATA SHEET P01 T.DOR/INST.1,2,3,4 & 5

ALL DIMENSIONS ARE NOMINAL & IN mm

© COPYRIGHT & DESIGN 2007 PROPERTY OF

KOMFORT WORKSPACE Plc
WHITTLE WAY, CRAWLEY, WEST SUSSEX, RH10 9RT
TEL : 01293 592500 WEB www.komfort.com
DO NOT SCALE IF IN DOUBT ASK



ISSUE	DESCRIPTION OF CHANGE	DATE	TITLE
		21:05:07	SINGLE GLAZED POLAR FIRE PERFORMANCE TIMBER DOOR
		SSG	HORIZONTAL DETAIL SJ35 DOOR FRAME
MATERIAL :	CHKD		DRAWING No
FINISH :	SCALE	NTS	13102
			ISSUE
			2