



FOR FIRE PERFORMANCE

CORRIDOR

DRAWING MUST BE READ INCONJUNCTION WITH SUMMARY OF PERFORMANCE DOCUMENT PO/F5 AND DATA SHEET PO2 G.DOR/INST.1,3 & 4

DOOR WIDTH DIM X	DISTANCE BETWEEN DGP4 & SJ3 BASE CHANNEL DIM Z
835 (SINGLE)	924

ALL GLASS MUST CONFORM AS REQUIRED TO BS 476:PART 22 BS 6262, BS 6206 & DOCUMENT 'N' BUILDING REGULATIONS

ALL DIMENSIONS ARE NOMINAL & IN mm



© COPYRIGHT & DESIGN 2007 PROPERTY OF
 KOMFORT WORKSPACE Plc
 WHITTLE WAY, CRAWLEY, WEST SUSSEX, RH10 9RT
 TEL : 01293 592500 WEB www.komfort.com
 DO NOT SCALE IF IN DOUBT ASK

ISSUE	DESCRIPTION OF CHANGE	DATE	04:06:07	TITLE	POLAR DOUBLE GLAZED 30min FIRE PERFORMANCE GLASS DOOR HORIZONTAL DETAIL DGP26 DOOR FRAME
MATERIAL :		DRAWN	SSG	DRAWING No	14086
FINISH :		CHKD		ISSUE	2
		SCALE	NTS		