



FOR FIRE PERFORMANCE

DRAWING MUST BE READ INCONJUNCTION WITH SUMMARY OF PERFORMANCE DOCUMENT PO/F10 AND DATA SHEET PO2 T.DOR/INST.2,3,4 & 5

TYPE	DOOR WIDTH	DISTANCE BETWEEN DGP4 & SJ3 BASE CHANNEL
		$Z = X + 86$
SINGLE	X	Z
	762	848
	826	912
HOSPITAL	838	924
	1145* (1½ x 762)	1231
DOUBLE	1259* (1½ x 838)	1345
	1526* (2 x 762)	1612
	1678* (2 x 838)	1764

* INCLUDES 2mm GAP BETWEEN DOORS

ALL GLASS MUST CONFORM AS REQUIRED TO BS 476:PART 22 BS 6262, BS 6206 & DOCUMENT 'N' BUILDING REGULATIONS

ALL DIMENSIONS ARE NOMINAL & IN mm



© COPYRIGHT & DESIGN 2007 PROPERTY OF KOMFORT WORKSPACE Plc WHITTLE WAY, CRAWLEY, WEST SUSSEX, RH10 9RT TEL : 01293 592500 WEB www.komfort.com DO NOT SCALE IF IN DOUBT ASK

DATE	05:06:07	TITLE	POLARTEC DOUBLE GLAZED DEFLECTION HEAD 30min FIRE PERFORMANCE TIMBER DOOR & OVER PANEL VERTICAL DETAIL DGP26 DOOR FRAME
ISSUE	DESCRIPTION OF CHANGE	DRAWN	SSG
MATERIAL :		CHKD	
FINISH :		SCALE	NTS
DRAWING No			14091
ISSUE			3