



**FOR FIRE PERFORMANCE**

DRAWING MUST BE READ INCONJUNCTION WITH SUMMARY OF PERFORMANCE DOCUMENT PO/F13 AND DATA SHEET P02 T.DOR/INST.6,7,8,9 & 10

ALL GLASS MUST CONFORM TO AS REQUIRED TO BS 476:PART 22 BS 6262, BS 6206 & DOCUMENT 'N' BUILDING REGULATIONS

DOOR WIDTH DIM X	DISTANCE BETWEEN SJ4 & SJ3 BASE CHANNEL DIM Z
838 (SINGLE)	936

ALL DIMENSIONS ARE NOMINAL & IN mm



© COPYRIGHT & DESIGN 2009 PROPERTY OF  
 KOMFORT WORKSPACE Plc  
 WHITTLE WAY, CRAWLEY, WEST SUSSEX, RH10 9RT  
 TEL : 01293 592500 WEB www.komfort.com  
 DO NOT SCALE IF IN DOUBT ASK

DATE	12:08:09	TITLE	POLARTEC DOUBLE GLAZED 30min FIRE PERFORMANCE TIMBER DOOR HORIZONTAL DETAIL TIMBER DOOR FRAME	
ISSUE		DRAWN	SSG	
MATERIAL :		CHKD	BJP	DRAWING No
FINISH :		SCALE	NTS	14117
				ISSUE 1