N'SSAE LL GLASS MUST CONFORM S REQUIRED TO BS 476:PART 22 SS 6262, BS 6206 & DOCUMENT N'BUILDING REGULATIONS DIMENSIONS ARE NOMINAL Ş ⋛

mm

DRAWING MUST BE READ INCONJUNCTION WITH SUMMARY OF PERFORMANCE DOCUMENT PO/FA -0R FIRE **PERFORMANCE**

G38 KOMFORT 12.4mm THICK INTUMESCENT FIRE SAFETY GLASS SJG1 INTUMESCENT GLAZING GASKET (DETAIL G3/G909, SJG2 INTUMESCENT GLAZING GASKET SJG1 INTUMESCENT INTUMESCENT FFL GLAZING CEILING **GASKET** MODIFIED GLAZING GASKET SJG2 16 9 **CORRIDOR** 80 79 DJ10104 - APPROVED TOUGHENED OR ACOUSTIC SAFETY GLASS DGP11 DGP4 SJ3 SJ12 NON COMBUSTABLE SETTING BLOCK SJ13 DGP1 3000 MAXIMUM



PROPERTY OF

KOMFORT
ASHURST,BROADLANDS BUSINESS CAMPUS
LANGHURST WOOD ROAD,
HORSHAM
WEST SUSSEX, RH12 4QP
TEL: 01403 390300 DO NO

C)COPYRIGHT & DESIGN 2104

WEB www.komfort.com DO NOT SCALE IF IN DOUBT ASK

		DATE	13:11:14	T
ISSUE	DESCRIPTION OF CHANGE	DRAWN	SSG	
MATERIAL :		CHKD		C
FINISH:		SCALE	1:1	

TITLE DOUBLE GLAZED POLAR
DRY JOINTED 30min FIRE PERFORMANCE VERTICAL DETAIL

DRAWING No

SP-1174

ISSUE