

At a glance

Dimensions:

Height - up to 3600mm Track width – 100mm Track height – 32mm

Fire ratings:

N/A

Acoustics:

Double glazed – up to 54dB (Rw)

Structure:

Up to severe duty

Deflection head:

+/-25mm

Door options:

Timber doors Single glazed doors Sonik doors

Glass type options:

Toughened – 10, 12mm Acoustic Lam. – 10.8, 12.8, 14.8mm Acoustic Lam. - 16.8

Toughened Lam. - 16.8
Triple Glazed Acoustic Lam.
- 6.8mm

Weight (excluding nominal head & base)*:

Toughened:

10mm = 25kg/m2

12mm = 30kg/m2

Acoustic Lam.:

10.8mm = 27kg/m $^{\circ}$

12.8mm = 32kg/m $^{\circ}$

14.8mm = 37kg/mÇ

16.8 mm = 42 kg/mÇ

Toughened Lam.:

17.5mm = 43.75kg/mÇ

✓ Blinds


✓ Manifestations

- ✓ Graphics
- ✓ SwitchGlass
- ✓ Kross Glaze

Paint/finishes

- ✓ Polyester powder coat
- X Satin anodised aluminium
- ✓ Special anodised finish
- dependent on system configuration / specification n

Polar 101



Polar 101 is Komfort's superior double glazed system which achieves our highest acoustic rating for when performance requirements are stringent. This system is available in a range of glass options and can be customised to meet unique requirements.

Introduced to meet the needs of busy working spaces, this system delivers unparalleled performance and beauty in design.

System specification

The Polar 101 double glazed system is the ultimate choice when acoustic and structural performance requirements are stringent. This system achieves our highest acoustic rating of 54dB (Rw) and can accommodate a range of customisable glass options. The offset profile takes 16.8mm-17.5mm glass on one side and 10-14.8mm on the other.

Similar to Polar 100, using the snap-in profile Polar 101 can fit a third pane of glass, a mesh panel, an LED screen and more. Polar 101 is compatible with Komfort's Sonik, glazed and timber doors. For an industrial aesthetic, this system is available with a range of Kross Glaze options including internal only and internal with applied bars.


Think partitioning, think Komfort.

Tel: +44 (0)121 332 2560 Email: headoffice@komfort.com **Technical Support**Email: technical@komfort.com

www.komfort.com



Polar 101




Head track (K101HT)

16.8-17.5mm Glass

10-14.8mmGlass

Glazing bead (K54GB)

Floor track (K101FT)



Triple glaze infill (K100TGI)

10-14.8mm Glass

6.8mm Glass

16.8-17.5mm Glass

Standard Double Glazed Head and Base Detail




Deflection head channel (K100DHC)


Deflection head (K101DH)

Glazing bead (K54GB)

Floor track (K101FT)



Standard Triple Glazed Head and Base Detail




Head track (K101HT)

Door frame (K101DF)

Door seal (K54DS)

Floor track (K101FT)

Standard +/-25mm Deflection Head and Base Detail



Head track (K101HT)


Applied bars (109)

Kross Glaze internal (K101KGI)

Glazing bead (K54GB)

Floor track (K101FT)

Double Glazed Door Frame Detail



Double Glazed with Kross Glaze Internal

Double Glazed with Applied Kross Glaze

Think partitioning, think Komfort.

Birmingham Office/Head Office

Tel: +44 (0)121 332 2560 Email: headoffice@komfort.com

Technical Support

Email: technical@komfort.com www.komfort.com