



NON FIRE PERFORMANCE ONLY

SEE SUMMARY OF PERFORMANCE & SEPERATE INSTRUCTION DATA SHEETS FOR ADDITIONAL COMPONENTS, INTUMESCENTS & SEALS TO OBTAIN ACOUSTIC & FIRE PERFORMANCE

ALL DIMENSIONS ARE NOMINAL & IN mm

MANIFESTATION TO GLASS FROM THE FINISHED FLOOR LEVEL MUST BE INSTALLED IN ACCORDANCE WITH PART 'M' BUILDING REGULATIONS



© COPYRIGHT & DESIGN 2011 PROPERTY OF KOMFORT WORKSPACE
 ASHURST, BROADLANDS BUSINESS CAMPUS,
 LANGHURST WOOD ROAD, HORSHAM, WEST SUSSEX, RH12 4QP
 TEL : 01403 392300 WEB www.komfort.com

DO NOT SCALE IF IN DOUBT ASK

4	GEN REVISION	DATE	14:06:11	TITLE	LS90 WALL ABUTMENT TO DOUBLE GLAZED USING 6mm TOUGHENED SAFETY GLASS
ISSUE	DESCRIPTION OF CHANGE	DRAWN	DDS	DRAWING No	
MATERIAL :		CHKD	BJP	21018	ISSUE
FINISH :		SCALE	NTS		4