



CAVITY WILL ACCEPT OFFSET
15mm & 25mm VENETIAN BLINDS
WITH REPLACEMENT OF
APPROPRIATE ELEMENTS

DIM Y = MODULE WIDTH
DIM X = DOOR WIDTH
DIM Y = DIM X + 160

TYPE	DOOR WIDTH	DOOR MODULE WIDTH Y = X + 160	DISTANCE BETWEEN BASE TRACK Z = Y - 80
	X	Y	Z
SINGLE	940	1100	1020
DOUBLE	1840*(2 x 918.5)	2000	1920

* INCLUDES 3mm FOR CENTRE GAP BETWEEN DOORS

NON FIRE PERFORMANCE ONLY

SEE SUMMARY OF PERFORMANCE & SEPERATE
INSTRUCTION DATA SHEETS FOR ADDITIONAL
COMPONENTS, INTUMESCENTS & SEALS TO OBTAIN
ACOUSTIC & FIRE PERFORMANCE

ALL DIMENSIONS ARE NOMINAL & IN mm

THIS DOOR FRAME REQUIRES ADDITIONAL
COMPONENTS AND INTUMESCENTS TO
OBTAIN FIRE RATING

FOR COLDSMOKE REQUIREMENT TO
BS476:PART 31.1 FIT 868 DOOR SEAL &
565 THRESHOLD SEAL



© COPYRIGHT & DESIGN 2011 PROPERTY OF
KOMFORT WORKSPACE
ASHURST, BROADLANDS BUSINESS CAMPUS,
LANGHURST WOOD ROAD, HORSHAM, WEST SUSSEX, RH12 4QP
TEL : 01403 392300 WEB www.komfort.com

DO NOT SCALE IF IN DOUBT ASK

5	GEN REVISION	DATE	16:06:11	TITLE	LS90
ISSUE	DESCRIPTION OF CHANGE	DRAWN	DJE	DOOR FRAME TO DOUBLE GLAZED USING 6mm TOUGHENED SAFETY GLASS HORIZONTAL DETAIL	
MATERIAL :		CHKD	BJP	DRAWING No	ISSUE
FINISH :		SCALE	NTS	21023	5