



THIS DOOR FRAME REQUIRES  
ADDITIONAL COMPONENTS AND  
INTUMESCENTS TO OBTAIN FIRE RATING  
FOR COLDSMOKE REQUIREMENT TO  
BS476:PART 31.1 FIT 868 DOOR SEAL &  
565 THRESHOLD SEAL

### NON FIRE PERFORMANCE ONLY

SEE SUMMARY OF PERFORMANCE & SEPERATE  
INSTRUCTION DATA SHEETS FOR ADDITIONAL  
COMPONENTS, INTUMESCENTS & SEALS TO OBTAIN  
ACOUSTIC & FIRE PERFORMANCE

ALL DIMENSIONS ARE NOMINAL & IN mm



© COPYRIGHT & DESIGN 2011 PROPERTY OF  
KOMFORT WORKSPACE  
ASHURST, BROADLANDS BUSINESS CAMPUS,  
LANGHURST WOOD ROAD, HORSHAM, WEST SUSSEX, RH12 4QP  
TEL : 01403 392300 WEB www.komfort.com

DO NOT SCALE IF IN DOUBT ASK

5	GEN REVISION	DATE	21:06:11	TITLE	LS90 WALL ABUTMENT TO DOOR FRAME
ISSUE	DESCRIPTION OF CHANGE	DRAWN	DJE	DRAWING No	21040
MATERIAL :		CHKD	BJP	ISSUE	5
FINISH :		SCALE	NTS		